

**GALAXY "GX"**


For illustrative purposes only

**ENGINE**

Description	DOOSAN
Engine model	D18
Cylinders	4
RPM speed	1500
Cubic capacity	1.79 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Optional voltage	Vdc
Sae	4-10
BMEP	0 kPa
Cooling	Water
Flywheel P.R.P. Power net	25.3 kW
Flywheel Stand-by Power net	27.6 kW
Fuel Cons. at 100% (L.T.P.)	7.9 l/h
Fuel Cons. at 100% (P.R.P.)	7.4 l/h
Fuel Cons. at 75% (P.R.P.)	5.6 l/h
Fuel Cons. at 50% (P.R.P.)	3.8 l/h
Fuel Cons. at 25% (P.R.P.)	2.2 l/h
Electronic regulator	Standard
Precision class	G2
Oil quantity	6.3 l
Engine Antifreeze capacity	3.1 l
Radiator type	TE
Heat from radiator	29.7 kW
Heat from exhaust	0.0 kW
Heat from radiation	0.0 kW
Exhaust temperature	750 °C
Cooling air flow	1.9 m <sup>3</sup> /min
Combustion air flow	0.0 m <sup>3</sup> /min
Exhaust gas flow	0.0 m <sup>3</sup> /min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	5

**MAIN DATA**

Continuous power (PRP)	<b>30.00</b> kVA
Continuous power (PRP)	<b>24.00</b> kW
Stand-by power (LTP)	<b>32.00</b> kVA
Stand-by power (LTP)	<b>25.60</b> kW
VAC - HZ - cos(fi)	<b>400 - 50 - 0.8</b>

**DIMENSIONS AND WEIGHT**

Width	1040 mm
Length	2260 mm
Height	1805 mm
Weight	1030 kg

**ALTERNATOR**

Description	STAMFORD
Alternator model	S0L2-P
P.R.P. Power	30 kVA
L.T.P. Power	33 kVA
Connection	Series star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS540
Precision	1 ± %

**BASEFRAME**

Model	GV030HD
Standard tank	160 l
Optional tank	70 l

**CANOPY & SILENCER**

Canopy model	GV030
Silencer model	MSR/a 50
Silencer outlet diameter	60 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.  
**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

